

MVG 12/140



Battery Technology NZ Ltd
PO Box 907 Whangaparaoa Auckland New Zealand
sales@batterydirect.co.nz www.batterydirect.co.nz
++ 64 9 428 0863

Product code: 64001400

In Gel batteries, the electrolyte is absorbed by a Gel. This type of battery is entirely maintenance-free and has no gas formation with normal use. As no extra ventilation is required, Gel batteries can be installed anywhere. They are ideal as service battery and for cyclical use, and can be charged very quickly.

- Perfect service battery for medium sized and large 12 V and 24 V systems.
- Extremely long lifespan.
- No gas formation with normal use.
- Fast recharge, high charge current possible.
- For intensive cycle use with a high number of charge/discharge cycles.
- Very low self-discharge.
- High return on investment.
- Two year warranty.

Specifications

General specifications

Nominal battery voltage	12 V
Nominal battery capacity C20 (battery capacity at a discharge time of 20 hours, till 10.5 V per battery)	140 Ah
Max. charge current	70 A
Battery terminals	A-type
Max. outer dimensions (incl. terminals/grip handles), l x w x h	513 x 223 x 223 mm 20.2 x 8.8 x 8.8 inch
Weight	49 kg 108.0 lb

Technical specifications

CCA to DIN	540 A
CCA to SAE	920 A